

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An apparatus~~A wellbore system~~ for producing seismic energy in an earth formation, comprising:
 - (a) a cavity in the apparatus configured to be disposed in a wellbore; and
 - (b) a drive source in fluid communication with the cavity, the drive source configured to inject fluid under pressure into the cavity to generate pressure waves in said cavity, the cavity producing seismic waves in the earth formation in response to the pressure waves, wherein the fluid circulates from the drive source to~~between~~ the cavity and back to the drive source in a closed loop manner.
2. (Currently Amended) The apparatus~~wellbore system~~ of claim 1 wherein said drive source is configured to generate pressure waves at a selected resonance frequency of said cavity.
3. (Currently Amended) The apparatus~~wellbore system~~ of claim 1 wherein said drive source includes at least one of (i) a rotary valve, (ii) an electro-solenoid oscillator, and (iii) a pump.
4. (withdrawn) The apparatus~~wellbore system~~ of claim 1 wherein said drive source for generating pressure waves is activated in a range of predetermined frequencies to create a swept frequency signal input.
5. (withdrawn) The apparatus~~wellbore system~~ of claim 4 wherein said swept frequency signal input is at least one of: i) an up-sweep, ii) a down-sweep, iii) a nonlinear sweep, a psuedo-random sweep and iv) a random sweep.
6. (Currently Amended) The apparatus~~wellbore system~~ of claim 1 further comprising seismic sensors configured to record said produced seismic waves.
7. (Currently Amended) The apparatus~~wellbore system~~ of claim 1 wherein said fluid is at least one of: (i) a liquid, and (ii) a gas.
8. (withdrawn) The apparatus~~wellbore system~~ of claim 1 wherein said cavity is shaped to provide a broad frequency signal for said seismic waves in said earth formation.
9. (Currently Amended) The apparatus~~wellbore system~~ of claim 1 wherein said fluid comprises a smart fluid.

10. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 9 further comprising at least one coil provided adjacent said cavity, said coil configured to provide an excitation field for said smart fluid in said cavity when energized.
11. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 10 wherein an effective length of said smart fluid in said cavity can be controlled by selectively energizing said coil.
12. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 11 wherein said at least one coil includes a plurality of segments, each of which can be separately energized.
13. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 10 wherein said at least one coil is configured to provide an adjustable magnitude of intensity for said excitation field.
14. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 10 further comprising a control unit operably coupled with one of said drive source and said coil.
15. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 14 further comprising at least one sensor connected to said control unit, said at least one sensor configured to measure a selected parameter of interest.
16. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 15 wherein said selected parameter of interest is selected from a group consisting of (i) pressure, (ii) temperature, (iii) seismic energy, (iv) flow rate, and (v) frequency of pressure signals generated by said drive source.
17. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 15 wherein said control unit is configured to adjust said drive source in response to a measurement provided by said at least one sensor.
18. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 1 further comprising a control unit operable coupled with said drive source.
19. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 18 further comprising at least one sensor connected to said control unit, said at least one sensor configured to measure a selected parameter of interest.
20. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 19 wherein said selected parameter of interest is selected for a group consisting of (i) pressure, (ii)

temperature, (iii) seismic energy, (iv) flow rate, and (v) frequency of pressure signals produced by said drive source.

21. (Currently Amended) The ~~apparatuswellbore-system~~ of claim 19 wherein said control unit is configured to adjust said drive source in response to a measurement provided by said at least one sensor.

22. (Currently Amended) A method for producing seismic energy in an earth formation, comprising:

- (a) ~~conveying an apparatus including~~providing a cavity in a wellbore;
- (b) injecting a fluid under pressure into the cavity with a drive source in the apparatus to generate pressure pulses in the cavity such that the cavity produces seismic waves in an adjacent earth formation; and
- (c) circulating the fluid ~~frombetween~~ the drive source to the cavity and back to the drive source in a closed loop manner.

23. (Currently Amended) The ~~methodwellbore-system~~ of claim 22 wherein the fluid is injected in a manner that causes the cavity to resonate.

24. (Original) The method of claim 23 wherein the drive source includes at least one of (i) a rotary valve, (ii) an electro-solenoid oscillator, and (iii) a pump.

25. (Original) The method of claim 22 wherein the fluid comprises a smart fluid.

26. (Original) The method of claim 25 further comprising providing an excitation field for the smart fluid in the cavity using at least one coil.

27. (Original) The method of claim 26 further comprising controlling an effective length of the smart fluid in the cavity by selectively energizing the at least one coil.

28. (Original) The method of claim 26 wherein the at least one coil includes a plurality of segments, each of which can be separately energized.

29. (Original) The method of claim 25 further comprising controlling the injection of the fluid with a control unit.

30. (Original) The method of claim 29 wherein the injection is controlled in response to a measured parameter of interest.

31. (Original) The method of claim 30 wherein the measured parameter of interest is selected from a group consisting of (i) pressure, (ii) temperature, (iii) seismic energy, (iv) flow rate, and (v) frequency of pressure signals produced by the drive source.

32. (Original) The method of claim 22 further comprising a controlling the injection of the fluid with a control unit.
33. (Currently Amended) The apparatus~~wellbore—system~~ of claim 1 further comprising a tubular positioned in the wellbore configured to convey a fluid to a surface location, and wherein the cavity is configured to be positioned external to the tubular.
34. (Previously presented) The method of claim 22 further comprising positioning the cavity external to a tubular configured to convey a fluid to a surface location.
35. (Currently Amended) The apparatus~~wellbore—system~~ of claim 1 further comprising a fluid reservoir and a pump, wherein the fluid circulates from the reservoir to pump and from the pump to the cavity.
36. (Previously presented) The method of claim 22 further comprising circulating the fluid from a reservoir to pump and from the pump to the cavity.